

MATERIAL SAFETY DATA SHEET

Section I

Company Name: Future Graphics, LLC.
Address: 1175 Aviation Place
City, State, Zip Code: San Fernando, CA 91340
Phone for Information: 818 / 837-8100
EMERGENCY CONTACT: FUTURE GRAPHIC: 818 / 837-8100, 800 / 394-9900
Product Code: NP6030CART500
Description: LB TNR CART CANON NP6025 500g
Date Revised: 7/24/2003
Trade Name: Dry Toner
Chemical Name and Synonyms: None

HAZARDOUS INGREDIENTS / IDENTITY INFORMATION

Section II

| Hazardous Components (Chemical Identity : Common Names) | OSHA PEL | ACGIH TLV | Other Limits | (Optional) |
|---|----------------------|-----------------------|--------------|--------------|
| | | | Recommended | % |
| Styrene/Acrylic Resin (CAS # 25153-46-2) | not listed | not listed | | 85-95% |
| Carbon Black (CAS # 1333-86-4) | 3.5mg/m ³ | 3.5mg /m ³ | | 5-10% |
| Organic pigment (CAS # 116810-46-9*) | 10mg /m ³ | 10mg/m ³ | | 1-5% |
| Silica (CAS # 7631-86-9) | 6mg/m ³ | 10mg /m ³ | | <1% |
| Wax (CAS # 9003-07-0) | not listed | not listed | | |

PHYSICAL / CHEMICAL CHARACTERISTICS

Section III

Boiling Point (F): Not Applicable
Specific Gravity (Water = 1): 1.0-1.3
Vapor Pressure (mm HG): Not Applicable
Melting Point: 150-170 Deg C
Vapor Density (Air = 1): Not Applicable
Evaporation Rate (Butyl Acetate =1): Not Applicable
Solubility in Water: Insoluble
Appearance & Odor: Fine black powder, practically odorless.

FIRE & EXPLOSION HAZARD DATA

Section IV

Flash Point (Method Used): Not Applicable
Flammable Limits: Not Applicable
LEL: Not Applicable
UEL: Not Applicable
Extinguishing Media: Water, Foam , Dry Chemical, Co2
Special Fire Fighting Procedures: Avoid inhalation of smoke , Wear MSHA / NIOSH S.C.U.B.A
Unusual Fire and Explosion Hazards: None under normal storage and use conditions.

Reactive Data

Section V

Stability: Unstable: Stable: X
Conditions to Avoid: No Data
Incompatibility (Materials to Avoid): None
Hazardous Decomposition or Byproducts: Only after combustion
Hazardous Polymerization: Will Occur: Will Not Occur: X

| | |
|-----------------------------|---|
| Company Name: | Future Graphics, LLC. |
| Address: | 1175 Aviation Place |
| City,State,Zip Code: | San Fernando, CA 91340 |
| Phone for Information: | 818 / 837-8100 |
| EMERGENCY CONTACT: | FUTURE GRAPHIC: 818 / 837-8100, 800 / 394-9900 |
| Product Code: | NP6030CART500 |
| Description: | LB TNR CART CANON NP6025 500g |
| Date Revised: | 7/24/2003 |
| Trade Name: | Dry Toner |
| Chemical Name and Synonyms: | None |

HEALTH HAZARD DATA

Section VI

| | |
|--|---|
| Threshold Limits: | No Data |
| Routes of Entry: | |
| Eyes: | Possible |
| Inhalation: | Possible |
| Skin: | None Known |
| Ingestion: | Possible |
| Health Hazards (Acute or Chronic): | Minimal, being neither irritation,corrosive, volatile, nor toxic. Mutagenicity is negative. |
| Carcenogenicity: | None Present |
| NTP: | None Listed |
| IARC Monographs: | NO |
| OSHA Regulated: | NO |
| Signs or Symptoms of Exposure: | Contact with eyes may cause irritation, ingestion - gastric disturbances. |
| Medical Conditions Aggravated by Exposure: | None Known |

EMERGENCY AND FIRST AID PROCEDURES:

| | |
|--------------------|---|
| EYES: | Flush with water for 15 minutes. If irritation develops, get medical attention. |
| INHALATION: | Remove from exposure. If irritation develops, get medical attention. |
| SKIN: | Wash with soap and water. If irritation develops, get medical attention. |
| INGESTION: | Dilute stomach contents with several glasses of water. |

PRECAUTIONS FOR SAFE HANDLING AND USE

Section VII

| | |
|---|--|
| Steps to be Taken in Case Material is Released: | Loose toner can be removed by using vacuum cleaner or broom. Residue can be removed with soap and water. |
| Waste Disposal Method: | Do not incinerate. Dispose of in accordance with federal, state, and local regulations. |
| Precautions to be Taken in Handling or Storage: | Eye protection and respirators may be required for bulk handling. Avoid storing next to strong oxidizers. |
| Other Precautions: | Avoid excessive exposure to to heat |

CONTROL MEASURES

Section VIII

| | |
|---|---|
| Respiratory Protection: | Follow Federal and State guide lines for respirator selection and use. |
| Ventilation: | |
| Local: | Local exhaust ventilation is preferred for controlling dispersion at source |
| Mechanical: | No Data |
| Special: | No Data |
| Other: | Provide general or local exhaust ventilation to maintain below OSHA PELs |
| Protective Gloves: | Wear chemically protective gloves,boots,aprons and gauntlets |
| Eye Protection: | Wear protective eyeglasses or chemical safety goggles |
| Other Protective Clothing or Equipment: | None required. |
| Work / Hygienic Practices: | Wash hands with soap and water prior to eating. |

SPECIAL INSTRUCTIONS

This information is believed to be true and accurate. It represents the best information currently available to us. We make no warranty , expressed or implied with regard to such information. We make no liability resulting from its use. Users should make their own investigations to determine the suitability for their particular purposes.